

Easy to transport

GENIE TRAILER-MOUNTED BOOMS



Customers First Always

Partnering for Success

Our dedication to lifting you higher extends well beyond the physical reach of our products. We thrive on building satisfying customer relationships. Because you, our customer, are at the center of everything we do.

Since 1966, we've been developing products to solve your worksite challenges — and that process never ends. Our team of product managers and engineers uses your input to design new products, featuring the latest technology to meet your changing needs. Then we manufacture those products to stringent standards that help increase quality, lower costs and give you exceptional value for years to come.

Providing Superior Value

Our commitment doesn't end with the sale. Our dedicated service teams provide support when you need it most. Our extensive parts network ships most parts within 24 hours. Simply put, we're always working to help increase your "up time" so you can be more successful.

Genie is driven by one goal: doing the right thing, at the right time for our customers. That's not just what we do; it's who we are. So tell us what you need. We're listening.



Setting the Standard: Terex Aerial Work Platforms (AWP) manufactures some of the most advanced, highest-valued lift equipment in the industry. Distinctive blue Genie® lifts set the standard for performance and durability — not to mention support from people who understand your business.



Extend Your Productivity

Genie® trailer-mounted Z™-booms feature an outstanding operating envelope, making them your best value to reach jobs high and low. Both the Genie® TZ™-34/20 and the TZ™-50 feature the exclusive Genie® Automatic Levelling System™ for self-levelling on any terrain, resulting in a faster setup that gets the job started — and finished — quicker. With easy-to-tow mobility and simple pictograph controls, it's no wonder that Genie® trailer-mounted Z™-booms take productivity to new heights.

Versatile Genie® trailer-mounted Z™-booms offer an outstanding operating envelope with working heights of 12.36 to over 17 m (40 to over 55 ft) and superior outreach of 5.59 to over 8.8 m (18 ft 4 in to over 29 ft).

Reach Up Reach Out

The Genie® TZ™-34/20 has an outstanding working envelope and intuitive controls that allow operators to efficiently reach where they need to be. With a working height of up to 12.36 m (40 ft), an outreach of 5.59 m (18 ft 4 in) and 4.90 m (16 ft 1 in) of “up and over” capability, the TZ™-34/20 provides excellent versatility for a variety of jobs.



Easy Transport and Setup

The TZ-34/20 is easily towed behind 4x4 pick-up trucks. Hydraulic outriggers with automatic self-levelling allow machine setup in as little as 30 seconds, so you spend less time setting up and more time working.



Though rugged and heavy-duty, the TZ-34/20 is lightweight enough to use on lawns, slate or gymnasium floors. Simply put, it meets the challenges of just about any working environment.



Easy-to-Use Controls

Both ground and platform controls feature an easy-to-use pictograph system making it quick and easy to get right to work.



Designed For Serviceability


Easy setup and operation aren't the only efficient benefits of the TZ™-34/20. The machine is built to make service simple, including easy access to batteries. Simply release the clamp and remove the cover.



Built to Work

Durability is built in. The rigid chassis has a heavy-duty base and robust outriggers, making it the best solution for large and small contractors, maintenance crews, painting contractors and rental yards.

Versatile Working Range



For the ultimate in towable reach and range, you can't beat the Genie® TZ™-50. With a working height of 17.09 m (55 ft 6 in), 8.89 m (29 ft 2 in) of outreach and 6.71 m (22 ft) of "up and over" clearance, the numbers speak volumes about the versatility of the TZ-50. The fact that it's a favorite with contractors and rental yards says even more.



Compact Narrow Versatility


The TZ-50 offers outstanding "up, out and over" capabilities in a compact, lightweight package that is easy to manoeuvre in congested work areas. An assortment of options and accessories means you can customize the versatile TZ-50 to meet your exact needs.

The TZ-50 provides high value in high reach lift equipment.




Mobility

The TZ™-50 goes where you need thanks to its easy towing behind a 4x4 pick-up truck. — and heavy-duty jockey wheels for precise positioning during setup.



Flexible Working Range

Along with the primary jib boom, the articulating jib boom provides an additional 1.25 m (4 ft 1 in) of horizontal reach and 135° of working range to position the platform above or below horizontal.



Simple Levelling and Controls

Our patent-pending Automatic Levelling System™ allows the operator to hydraulically deploy the outriggers and level the machine to one degree in all directions. Plus, easy-to-use pictographs on both ground and platform controls offer simple, intuitive operation.



Designed For Serviceability

From transport and setup to operation and service, the TZ-50 keeps it simple, including easy access to batteries. Simply release the clamp and remove the cover.

Options And Accessories

| | TZ™ -34/20 | TZ-50 |
|--|------------|-------|
| Platform Options | | |
| PLATFORM ROTATION* | • | • |
| Power Options | | |
| DC | • | • |
| HYBRID DC/PETROL | | • |
| Drive | | |
| PORTABLE DRIVE CONTROL BOX | | • |
| Accessories | | |
| TOOL TRAY | • | • |
| FLUORESCENT TUBE CADDY | • | • |
| BATTERY CHARGE INDICATOR (BCI) | • | • |
| OPERATIONAL WARNING LIGHT PACKAGE (FLASHING BEACONS) | • | • |
| NON-MARKING OUTRIGGER FOOTPADS | • | • |
| SPARE TIRE | • | • |
| HORN | • | • |
| BICYCLE GUARD (CE) | • | • |



* 90° mechanical platform rotation on TZ-34, 160° hydraulic platform rotation on TZ-50.



Optional Platform Rotation

A manual rotate mechanism allows the operator to rotate the TZ™-34/20 platform a total of 90°, 45° in either direction. The hydraulic rotation on the TZ-50 provides a 160° of platform rotation.



Dual Flashing Beacons

Orange flashing lights warn workers when lift is moving or in operation.



Hitch Coupler

50 mm ball coupler is standard.

Options And Accessories



Hybrid DC/Petrol Engine

Allows machine to charge in remote locations.



Specifications

Trailer-Mounted Z™-Boom Lifts

| MODEL | WORKING HEIGHT | | HORIZONTAL REACH | | LIFT CAPACITY* | | | |
|-------------------------|----------------|------------|------------------|------------|-------------------|----------|---------------------------------|----------|
| | | | | | STANDARD PLATFORM | | WITH OPTIONAL PLATFORM ROTATION | |
| | | | | | CE | | CE | |
| | METRIC | IMPERIAL | METRIC | IMPERIAL | METRIC | IMPERIAL | METRIC | IMPERIAL |
| TRAILER-MOUNTED Z-BOOMS | | | | | | | | |
| TZ-34/20 | 12.36 m | 40 ft | 5.59 m | 18 ft 4 in | 200 kg | 440 lbs | 181 kg | 400 lbs |
| TZ-50 | 17.09 m | 55 ft 6 in | 8.89 m | 29 ft 2 in | 200 kg | 440 lbs | 200 kg | 440 lbs |

*Lift capacity varies depending on options and country standards.





Corporate Headquarters: United States

18340 NE 76th Street, P.O. Box 97030, Redmond, Washington 98073-9730

Telephone **+1 (425) 881-1800** • Fax +1 (425) 883-3475

www.genielift.com

Europe, Middle East, Africa and Russia

To view all our locations visit www.genielift.co.uk/locations

Telephone **(+44) 800 988 3739** (Toll Free for UK/Ireland) • Fax +31 165 511 148 • Email: AWP-InfoEurope@terex.com

www.genielift.co.uk

Worldwide Manufacturing And Distribution

Australia • Brazil • Caribbean • Central America • China • France • Germany • Italy • Japan • Korea • Mexico

Russia • Southeast Asia • Spain • Sweden • United Arab Emirates • United Kingdom • United States

Effective Date: February, 2014. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie and Taking You Higher are trademarks of Terex Corporation or its subsidiaries. © 2014 Terex Aerial Work Platforms. Part No. 109302UK.

